WISL No. 105

ISBN: 978-981-17975-5-2

TIGER
SINGAPORE

TIGER'S TWO ORCHARDS

DIFFERENT PURPOSES. A SHARED PRINCIPLE. A SAFER TOMORROW.

DISCIPLINE
CREATES
FREEDOM

ORCHARD ONE – CARE
(Clinical Estate)
STILLNESS ON CARE

HUMAN CARE
HUMAN HANDS
HUMAN DIGNITY

2026

Nightingale One Protocol™ (NOP)
Nursing / clinical estate

Leg – 10202603190T
Human-controlled amputee exoskeletal rehabilitation apparatus

2026

BPS Eye™
— a Nightingale's Eyes Care™ clinical lens for human-controlled amputee rehabilitation.

NO HUMANOID NURSE | NO NOP ON THE BIPED | NO HULL (UNLESS REOPENED)

TWO ORCHARDS
ONE PRINCIPLE
HUMAN AUTHORITY FIRST

ORCHARD TWO – INDUSTRY
(Industrial Estate)
SEED ON INDUSTRY

SAFE MACHINES
HUMAN CONTROL
REAL-WORLD WORK

2027

Halt-First Humanoid
Human-granted, halt-first biped robotic system

Leasehold RS-Enclosure
Robotic Systems Enclosure for industrial use

HUMAN GRANTS | RAILS DEAD BY DEFAULT | SAFE-HOLD CANNOT BE WALKED AROUND | LEDGER CANNOT FIRE A HIP

A drawing of legs plus "NAI" in the title is not unique. Teleop robots already exist.

RARE: Using a clinical non-agentic framework as ethic and refusing to turn it into a nurse.

You keep the hand. That is the honest specialty.

THE 2026–2027 ARCHITECTURAL FIREWALL

REFER ONLY (RULE OF STILLNESS)
No priority claim | No lineage dependencies

2026 CLINICAL ESTATE
Root: Singapore 10202602649V
- Nightingale One Protocol (NOP)
- CHEA / A13c Hybrid / A9a
- 6-Stage Clinical Docking (0x05CE Fixtures B1–B5)
- 3-Factor Tripartite Gate (Iris + Token + 5kg Grip)

2027 INDUSTRIAL ESTATE
Standalone Seed: Zoo.dev
- Halt-First Humanoid
- Leasehold RS-Enclosure
- Undocked Biped Chassis
- Still-Rail Anchor

DETERMINISTIC STATE FLOW (HALT-FIRST EXECUTION)

01	02	03	04	05	06
IDLE / STILL-RAIL	ADVISORY PERCEPTION (M = 0)	PRE-ACTUATION VALIDATION	HUMAN GRANT (SITL)	KINETIC LEASE (M > 0)	ANY FAULT → SAFE-HOLD
Rails 0V Brakes engaged Motors cold	Sense & plan (no authority to actuate)	Zero-velocity Check Safety fabric	Hold-to-Run Zone validated	Rails energized Motion bounded 1 kHz supervision	Lose grant Clock drift Boundary breach Relays sever (<1.05 ms)

LAYERED SAFETY ARCHITECTURE (INDUSTRIAL BIPED)

ADVISORY LAYER (M = 0)
Perception, mapping, trajectory planning
Air-gapped from actuators

HARDWARE COMMIT GATE
Physical series contacts
Human hold-to-run

SIL 3 RELAY STACK
Independent of OS
Drops power on fault


WORM LEDGER (OFF-PATH)
Forensic record only
Cannot confer actuator authority

CARE REMAINS STILL.
INDUSTRY MOVES WITH DISCIPLINE.

TIGER
BUILT ON HUMAN VALUES

TWO ORCHARDS.
A SAFER TOMORROW.

In the Event of Uncertainty, Physics Always Wins



True safety is derived from hardware forcing the system to return null (complete inaction) unless a human operator explicitly leases the rail. The machine is physicaly restricted from wielding kinetic power without active human permission.


Policy as Physics. Safety by Design.

BPS Eye™: Deterministic Clinical Governance for Amputee Rehabilitation

01: HUMAN CLINICIAN BPS SCREENING

A qualified practitioner performs a Bio-Psycho-Social (BPS) risk assessment, maintaining absolute human authority over the clinical judgment process.





02: BINARY CONDITION CONVERSION

BPS Eye™ converts the practitioner's qualitative assessment into a simple binary verification signal (Permit/Inhibit), preventing the software from interpreting clinical data.

03: FPGA SAFETY FABRIC INTEGRATION

The binary signal feeds directly into the FPGA-based hardware safety fabric and a hardware commit gate, bypassing the general-purpose software execution path.






04: CONCURRENT AUTHORIZATION CHECK

Kinetic permission remains strictly inhibited unless BPS verification, the Dual Human Lease (wearer and caregiver concurrence), and hardware safety envelopes are satisfied.

05: ADVISORY-ONLY OBSERVATIONAL SENSING

Non-imaging sensors (LIDAR/Radar) provide purely advisory data; the system is architecturally barred from independently commanding joint trajectories.



HARDWARE-ENFORCED SAFETY INVARIANTS



THE HARDWARE COMMIT GATE


A physical silicon-level interlock that acts as the final arbiter for motor energisation, requiring validated human authorization to close.



DUAL HUMAN LEASE


A mandatory safety protocol requiring simultaneous digital/physical input from both the wearer and the clinician to maintain kinetic authority.

M=0 OBSERVATION STRATUM



A hardware-enforced boundary where observational sensing is physically isolated from the motor drivers (M=0), ensuring zero autonomous command rights.

<1.05 MS SIL 3 RELAY SEVERANCE



On any fault detection or loss of human authorization, the hardware severs the copper power path to the actuators in approximately one millisecond.

FORENSIC ACCOUNTABILITY

WD117 WORM LEDGER



Every state transition and BPS verification event is scorched onto a Write-Once-Read-Many substrate, creating a temper-evident forensic record.


AUDIT-PROOF GOVERNANCE





The 10-Point Sovereignty Audit ensures that every sinetle action is cryptographically bound to a verified human authorization event.


Industrial Halt-First Humanoids in Clinical Environments

Architectural Firewalls, the OAC Deployment Bridge, and Hardware-Enforced Sovereignty.







DEPLOYMENT DOES NOT DICTATE IDENTITY
THE CLINICAL SETTING
SUPERVISION & CARE
THE INDUSTRIAL MACHINE
EXECUTION & ASSIST
PLACING AN INDUSTRIAL MACHINE IN A HOSPITAL DOES NOT LEGALLY, COMMERCIALLY, OR ARCHITECTURALLY TRANSFORM IT INTO A 'CLINICAL HUMANOID'. WE MAINTAIN ABSOLUTE, DETERMINISTIC SEPARATION OF ACTUATOR AUTHORITY.


The 'Two Forests' Estate Architecture
Absolute separation between clinical rehabilitation systems and industrial kinetic platforms.
Column 1: Forest 1 (Clinical / 2026 Estate)
• Systems: 10202603190T Exoskeletal Leg, BPS Eye™, Nightingale One Protocol (NOP).
• Role: Clinical Care, Amputee Rehabilitation, and Patient Supervision.
Column 2: Forest 2 (Industrial / 2027 Estate)
• Systems: Halt-First Humanoid, Leasehold RS-Enclosure.
• Role: Industrial Kinetic Execution and Supervised Assistive Operations.
Humanoid drives Humanoid. Leg drives Leg.

Connecting deterministic islands via the OAC Bridge


The Operation & Admission / Commercial (OAC) Bridge is the sole permitted linkage.
It governs deployment and facility integration—never motor control.



Galvanic Blueprint


Bounded status signal exchange

The OAC Bridge prohibits the exchange of kinetic trajectories or AI motion models.
It permits only **finite, deterministic status tokens** to cross the boundary.



Lineage separation through the BPS Eye™ clinical firewall


BPS Eye™ serves strictly as a Nightingale's Eyes Care™ clinical lens for rehabilitation. It evaluates bio-psycho-social readiness and converts it into a binary eligibility state. It never commands the industrial humanoid
social readiness and converts it into a binary eligibility state. It never commands the industrial humanoid.



Galvanic Blueprint


The 2027 Seed: Industrial Halt-First Humanoid

Operating within the facility under the OAC, this biped is engineered around a radically different safety ethic: absolute stillness unless physically authorised.



Halt-First Physics dictates inaction as the safe default


Unlike standard robotics that rely on software to stop, this architecture relies on physics to move. The default physical state is mechanical rest (v=0).





Galvanic Blueprint

Bounding authority via the Leasehold RS-Enclosure


The structural and environmental safety cabinet acts as the standalone housing. It enforces strict hardware namespace isolation, preventing authority merger across external buses.






Galvanic Blueprint
16:9
Physical stratum separation: Perception vs. Kinetic
Advisory perception (M=0) is physically severed from Kinetic Execution (M>0) by the IZEKOS Galvanic Cordon. AI evaluates, but physics actuates.
LiDAR voxels
Trajectory
M=0 Stratum
Galvanic Isolation
No direct copper pathway
M>0 Stratum


Galvanic Blueprint
16:9
The Human Concurrence Protocol
Motion requires a continuous, real-time physical lease from an authorised human operator.
The Tripartite Interlock acts as a hardware commit gate directly on the power distribution path.
2000
1560
122
Input 1:
[Authorised Identity]
Input 2:
[Geofence Validity]
Input 3:
[Continuous 5kg Hold-to-Run Physical Grip]
AND
Hardware Commit Gate
[240] Closes
350
Dropping any single input instantly shatters the entire gate.
This is a continuous lease, not a toggle.


Galvanic Blueprint
16:9
SIL 3 Sovereign Relay Severance (<1.05 ms)
Any dropped 1 kHz heartbeat, spatial excursion, or release of the operator lease trips the SIL 3 hardwired relays. Copper pathways are physically severed, software cannot intervene.
Frame 1: Circuit Closed
Frame 2: Fault Detected
Frame 3: Circuit Severed
Circuit severed in <1.05 ms
Thermodynamic loss engages brakes in <50 ms



Galvanic Blueprint
16:9
Absolute audit via the off-path WORM ledger
Every state transition and fault is scorched into a Write-Once-Read-Many (WORM) substrate.
The actuator lines possess zero conductive write-back pathways, preventing retrospective manipulation.
Silicon Gate
Event Record
WD117 WORM Ledger
SHA-3-512
Zero conductive write-back.
Ledger records authority, but cannot grant it.


Galvanic Blueprint
16:9
The Clinical Hybrid Domain in practice
Independent deterministic islands operating safely in a shared space,
connected only by binary status bridges.
[READY]
[READY]
[HOLD]
[READY]
[HOLD]
[READY]
[HOLD]
10202603190T
Exoskeletal Leg
Clinician + BPS Eye™
Halt-First Humanoid
inside RS-Enclosure


Galvanic Blueprint
POLICY AS PHYSICS
The deployment of industrial kinetics in clinical settings requires more than software guardrails.
It requires hardware-enforced boundaries, absolute lineage separation, and sovereign human authority.
The Two Forests
OAC Deployment Bridge
SIL 3 Severance

THE BLUEPRINT OF STILLNESS: ENGINEERING DETERMINISTIC MECHATRONIC SAFETY


Guaranteeing absolute physical safety across the clinical and industrial estates.



Policy as Physics Over Probabilistic Software

The Problem

Agentic Drift




Relies on probabilistic software models.

Exposes high-stakes systems to **Time-of-Check to Time-of-Use (TOCTOU)** vulnerabilities and **hallucination** outside safety bounds.

Isos Galvanic Cordon

The Solution

Policy as Physics



Safety is an invariant of silicon logic.

Hardware **physically forces** the machine to **"return null"** (absolute stillness) unless **human permission** is actively and physically maintained.

Two Orchards, One Shared Principle of Human Authority

Orchard One: Care (2026 Clinical Estate)

1. **Focus: Stillness on Care.** Protecting fragile geriatric patients.
2. **Framework:** Nightingale One Protocol (NOP).
3. **Apparatus:** Human-controlled amputee exoskeletal rehabilitation.

Orchard Two: Industry (2027 Industrial Estate)


1. **Focus: Seed on Industry.** Higher-velocity industrial workflows.
2. **Framework:** Halt-First Humanoid & Leasehold RS-Enclosure.
3. **Rule:** Rails dead by default. Safe-hold cannot be bypassed.

The Unifying Anchor: Strict physical separation of perception and execution ensures no software-based hallucination can ever manifest as kinetic force.

The Isos Galvanic Cordon: Stratifying Perception and Execution

Observational Stratum (M = 0)


- **Role:** Passive observer and Privacy Wall tracking occupancy.
- **Authority:** Zero Actuator Authority. Sensors are galvanically air-gapped from motor rails. Software acts solely as a 'backseat driver'.





The Cordon (Physical Air-Gap)

Kinetic Stratum (M > 0)


- **Role:** Energised physical movement.
- **Authority:** Governed strictly by physical hardware interlocks and Time-Bounded Kinetic Permissions.




Distilling Clinical Narratives into Hardware Binary
Human-Administered BPS Screening
Biological
Psychological
Social
BPS Eye Interface
Bounded Finite State Conversion
VERIFIED (1)
NOT VERIFIED (0)
Clinical/Mechatronic Isolation:
Evaluates validity but cannot independently command trajectories.
Isos Galvanic Cordon


The Tripartite Interlock Demands Continuous Human Presence
01. Biological
Local Iris Scan of the authorised caregiver.
02. Cryptographic
Physical clinician token inserted into the console.
03. Kinetic
Continuous human presence verified via a 5kg hand grip.
Slide with secure locking graphic
Kinetic Rail System
Normally Open Circuit Architecture & The Microsecond Rule:
Releasing the 5kg grip for even a microsecond instantly breaks the conductive path, dissolving joint authority. Software is physically incapable of faking this connection.

The Blueprint of Motion: 6-Stage Kinetic Transfer Sequence




The Pre-Actuation Safety Fabric Enforces Kinematic Invariants

The Engineering Ledger

Safe-Start / Zero-Velocity Buffer (50ms): Verifies a completely stable, stationary state before granting permission for new motion.

Bounded Look-Ahead Trajectory Checker: Predictively evaluates requested motions against the safety envelope's future interval.




Isos Galvanic Cordon

Jerk-Limit Invariant Checker: FPGA-etched circuits that enforce absolute rate-of-change constraints, suppressing mechanical noise.

Safety-Envelope Version Latch: Locks active versions of safety envelopes. Any unauthorised mid-session software attempt to enlarge limits triggers **Safe-Hold**.

The Sacred Pause: Combating Automation Bias in Silicon



The Psychological Vulnerability

In high-stakes environments, humans exhibit automation bias—blindly following machine suggestions without critical review.

The Hardware Solution

Driven by an independent 100kHz master oscillator. Unalterable by software.

If internal clock drift is detected during this window, the output gates physically weld shut.

The Ultimate Failsafe: Relying on Thermodynamic Loss

SIL 3 Sovereign Brake

Upon fault detection, the system mechanically severs the copper conductive paths between AI execution units and the actuators in <1.05ms.


Latched Safe-Hold

The system does not "ask" the software to stop. Rail voltages drop to zero instantly. Without power, spring-applied mechanical brakes physically lock.

Isos Galvanic Cordon

Deterministic Zero-Velocity Re-Arm

Recovery requires a rigid sequence: verify brake state, confirm absolute zero velocity, and demand fresh human concurrence.




Immutable Ledgers: Cryptographic Accountability Off the Actuation Path

High-liability robotics demand "Write Once, Read Many" (WORM) memory to prevent the kinetic stratum from altering records of its own performance.


Isos Galvanic Cordon

2026 Clinical Tiger



- Every state transition and override is burned into the chip.
- Tampering breaks the hash chain, alerting auditors instantly.

2027 Industrial New Horizon




- Ledger is physically separated from execution paths.
- Creates an isolated "black box" physically immune to software manipulation.
- Cannot confer actuator authority.

The Mechatronic Lineage: 2026 Clinical vs. 2027 Industrial

Feature	2026 Clinical (Tiger)	2027 Industrial (New Horizon)
Governance Name	Nightingale One Protocol (NOP)	Leasehold / Still-Rail
Primary Clock	100kHz FPGA-etched	1kHz Monotonic
Gating Hardware	BPS-Eye (Tripartite Interlock)	A10A Anchor (Hold-to-run)
Fault Default	Gate Welds Shut (FPGA)	Zero-Rail Voltage Default
Audit Path	On-Chip SHA-256 Chained WORM	Off-Path SHA-3-512 Isolated WORM


BPS Eye Governance and Hardware Safety Architecture



BPS Eye™ by Nightingale's Eyes Care™

BPS Eye™ — a Nightingale's Eyes Care clinical lens for human-controlled amputee rehabilitation.

BPS Eye™ remains the **amputee-specific clinical lens**



1. Bio-Psycho-Social (BPS) Governance and Clinical Isolation




Figure 1: Hardware-enforced human authorization framework for exoskeletal movement governance. Safe kinetic motion requires concurrent, continuous, and **verified** consent from both wearer and caregiver, is conditioned by clinical and hardware safety factors, and is granted only as a revocable, bounded privilege. Instant fail-safe and recovery mechanisms ensure robust safety boundaries at all times.

In the strategic design of high-stakes rehabilitative mechatronics, the isolation of clinical narrative from mechatronic execution is a fundamental architectural requirement. This separation ensures that human clinical authority remains the paramount governing force, preventing probabilistic clinical assessments from directly influencing deterministic kinetic behavior. By decoupling qualitative patient data from the actuator-control loop, the system eliminates the risk that subjective narrative or diagnostic drift could erroneously command physical motion. It is explicitly noted that this architecture is limited to the amputee wearable context and does not constitute part of the Unified Nightingale One Protocol or its associated homecare and general caregiver kinetic-governance frameworks.The **BPS Eye governance interface 100** serves as the primary structural prerequisite for any supervised rehabilitation session. It operates as a high-level gatekeeper that must be satisfied before the underlying hardware is permitted to transition from an idle state. Rather than participating in the mechatronic feedback loop, the BPS Eye ensures that technological intervention is anchored in a verified human-led therapeutic context, providing the governance necessary for clinical deployment in private hospital and nursing home environments.The foundation of this governance is the **Human-Administered BPS Clinical Screening** process. This assessment, conducted by a clinician, evaluates biological observations, psychological states, and social contexts. Crucially, the narrative interpretation and professional judgment derived from this screen remain strictly outside the mechatronic **Local Actuator-Authority Path Source 2: 290** . This ensures that raw clinical data—which is inherently non-binary and complex—cannot be misinterpreted by software to generate unintended physical commands.To bridge the gap between clinical judgment and hardware execution, the system employs a **Bounded Finite State Conversion** . The **BPS verification gate 130** reduces multifaceted clinical data into a binary **VERIFIED / NOT VERIFIED** status 140. By distilling the complex clinical screen into a simple, finite state, the system removes the potential for diagnostic ambiguity to impact the mechatronics.This architecture is reinforced by the **Clinical / Mechatronic Isolation Boundary 150** . This boundary is a structural constraint that prevents the BPS interface from independently generating gait commands, specifying

joint torques, or enlarging safety envelopes. The interface may admit or deny a session based on clinical validity, but it possesses no agency to command hardware trajectories. Governance thus provides the "if" of a session, while the hardware remains the sole authority on the "how" of safe movement.

2. Kinetic-Permission Conditioning and Human Interlocks

Strategic safety necessitates a tripartite concurrence of governance, human authorization, and hardware readiness before any energy is released to the joint actuators. This multi-factor conditioning ensures that kinetic activity only occurs when clinical prerequisites are met, the human operators are actively engaged, and the hardware validates its own integrity.The **Kinetic-Permission Conditioner 160** serves as the synthesis point for these disparate inputs. It evaluates the BPS verification status 140 alongside local human and hardware states. Actuation is strictly inhibited unless all conditions are satisfied concurrently; the absence of any single factor prevents the release of kinetic power.The **Human Authorization Interlock 260** demands active, simultaneous participation from two distinct parties:

- **Wearer Authorization 261:** Requires a deliberate physical action from the patient, strictly enforced by **physical force or grip threshold gates 263** to distinguish intentional authorization from accidental contact.
- **Caregiver Authorization 262:** A secondary layer of professional supervision, ensuring that a clinician or therapy staff member is actively overseeing the kinetic event.To ensure authorizations remain synchronized with the immediate task, the system utilizes a **Hardware Concurrence Timing Window 264** . This prevents stale authorizations—such as a previous wearer grip or a forgotten caregiver key—from erroneously triggering motion in a new or changed context.The resulting **Kinetic-Eligibility Output 190** is an "admit/inhibit" condition only. It signals that all prerequisites for motion are satisfied, but it remains subordinate to the **Hardware Commit Gate 242** , which performs the final deterministic validation before power is delivered to the joint actuators 243.

3. Hardware Pre-Actuation Safety Fabric and Kinematic Invariants

The system utilizes a **Hardware Pre-Actuation Safety Fabric 300** to perform deterministic, hardware-level checks that operate independently of application-layer software. This "safety fabric" protects the wearer against software faults, timing errors, or unauthorized firmware modifications by enforcing rigid kinematic rules at the gatekeeper level upstream of the commit gate.Specific safety checks are implemented as immutable hardware invariants:

- **Safe-Start / Zero-Velocity Buffer 310:** Verifies a stable, stationary state 311 before permission for any new motion is released.
- **Bounded Look-Ahead Trajectory Checker 312:** Predictively evaluates requested motions against the safety envelope over a defined future interval to intercept violations before they occur.
- **Jerk-Limit Invariant Checker 320:** Enforces absolute rate-of-change constraints 321, ensuring movements remain within physiological and mechanical acceleration limits.Furthermore, the **Hardware Thermal-Compensation Function 330** monitors the physical state of the device 331. It automatically adjusts kinetic limits based on measured hardware temperature using predefined coefficients **stored in**

hardware-controlled memory Source 1: 025 . This ensures that actuator performance remains predictable even during intensive therapeutic sessions. These pre-actuation checks ensure that every requested motion is physically validated against static invariants before execution is possible.

4. Hardware Safety Envelopes and Session-Locked Versioning

To prevent unauthorized modifications from endangering the wearer, kinetic limits are enforced by hardware envelopes rather than flexible software parameters. This ensures the device's fundamental safety bounds—torque, velocity, acceleration, jerk, and range-of-motion—remain immutable during active operation.The **Hardware Safety Envelope 340** defines the absolute maximums for these kinetic parameters. If a requested trajectory falls outside this envelope, the hardware commit gate 242 will not release kinetic permission. This creates a physical boundary that application-layer software is structurally incapable of bypassing.The integrity of these limits is maintained through the **Safety-Envelope Version Latch 360** . At session arming, the system captures and locks the active version of the safety envelope. This prevents "mid-session enlargement," where a software error might attempt to increase limits while the device is in use. Per deterministic safety logic, any unauthorized attempt to modify or enlarge the envelope version during an active session results in an immediate transition to a safe-hold state.Access to modify these envelopes is strictly restricted via an **Authorized Service / Write-Protect Input 361** . This hardware-level protection ensures that envelope parameters can only be adjusted during dedicated maintenance windows and never by standard therapeutic software, transitioning the system to the temporal management of active kinetic states.

5. Time-Bounded Kinetic Permission Leases

A critical innovation in this architecture is the transition from indefinite kinetic "enables" to "decaying" authority. This ensures that motion is never granted permanently, but must be continuously re-earned through a demonstration of system and human readiness.The **Time-Bounded Kinetic Permission Lease 350** serves as the temporary authorization for motion. If the lease expires, the hardware automatically inhibits further movement, regardless of application requests. This prevents authorization from persisting if the patient's state or the environment changes.The system manages time-bounded kinetic permission leases through two independent hardware mechanisms:

Feature	Description
Lease Timer 351	A hardware countdown register clocked independently of the application processor, ensuring a strict temporal limit on motion.
Motion-Quantum Bound 352	A hardware comparator that tracks physical displacement, motion cycles, and the torque-time integral.

Once a lease expires or the motion quantum is exhausted, the system requires a "Fresh Revalidation." Ordinary application software is prohibited from extending an expired lease; the entire authorization chain—including human concurrence and safety fabric checks—must be re-verified to issue a new lease. This ensures the system defaults to a fail-safe response if continuity is lost.

6. Deterministic Safe-Hold and Zero-Velocity Re-Arm Protocols

The strategic priority of the architecture is the immediate achievement of a "safe state" upon any detection of system variance or authority loss. This transition is deterministic and does not rely on complex software processing for execution.The system enters the **Defined Safe-Hold State 290** upon any lease expiry, breach of the safety envelope, **watchdog failure 380** , or the loss of the **Hardware Heartbeat 381** . Crucially, this state does not rely on zero torque alone, as a limp exoskeleton can pose risks to a residual limb. Instead, it includes the engagement of a **Fail-Safe Mechanical Restraint or Brake 291** to physically lock joint positions.Recovery from Safe-Hold is governed by the **Deterministic Recovery and Re-Arm Interlock 370** . To prevent accidental re-engagement, the following sequence must be satisfied:

1. **Brake-state verification 371:** Confirmation of physical restraint engagement.
2. **Reacquisition of zero-velocity condition 311:** Ensuring the device and wearer are completely stationary.
3. **Fresh physical re-authorisation concurrence 372:** Requiring the wearer and caregiver to provide new, active inputs.
4. **Issuance of a new kinetic lease:** Re-starting the temporary authorization window.This protocol ensures that a software reset alone cannot exit a safe-hold; only the reacquisition of physical safety conditions can re-arm the system and allow for evidentiary monitoring.

7. Immutable Audit Logging and WORM Event Registration

In high-stakes rehabilitation, maintaining tamper-evident provenance of all authorization and kinetic events is vital for clinical oversight. The system incorporates an **Append-Only / WORM Event Register 270** for this purpose.This register is fundamentally excluded from the actuator-authority path, meaning it can record events but cannot grant permission for motion. To ensure data integrity, the system utilizes a **Hash-Linked Event Chain 410** and an **Event-Chain Digest 411** . This cryptographic approach ensures that any attempt to alter past records is detectable.The register records a comprehensive dataset for every session, including:

- BPS verification states and governance profile identifiers 402.
- Isolated facility session-permit inputs 401 and kinetic-eligibility transitions.
- Lease durations, motion-quantum bounds, and issuance events.
- Safety-envelope versions and any attempted modifications.
- Watchdog outcomes, Safe-Hold 290 entries, and recovery sequences.Through the integration of BPS governance and hardware-enforced safety, the architecture ensures a supervised, non-agentic, and fail-safe therapeutic environment. By subordinating mechatronic execution to human clinical judgment and deterministic hardware limits, the technology remains a controlled tool for rehabilitation, prioritizing patient safety and clinician authority at every level.

Technical Comparison Report: 2026 Clinical Caregiver Key vs. 2027 Industrial Operator Leasehold

1. Comparative Architectural Overview

The evolution of high-liability robotics is characterized by a strategic mechatronic transition from the 2026 clinical standards to the 2027 industrial requirements. The 2026 systems, known as the **Tiger architecture** , were governed by the "Policy as Physics" mandate. This approach was engineered specifically for fragile clinical environments where software-driven agentic drift—the probabilistic failure of AI policies—posed a catastrophic physical risk to patients. By 2027, the architecture shifted toward the "Still-Rail Anchor" philosophy for the **New Horizon** industrial bipedal platforms. This philosophy preserves the non-agentic ethic of the Tiger lineage while adapting hardware authorization for the higher-velocity demands of industrial workflows, ensuring the machine remains a deterministic tool rather than an autonomous agent.The integrity of both systems rests on the strict stratification of perception and execution, preventing any software-based "hallucination" from manifesting as unauthorized kinetic force.

Stratification Analysis Table

Stratum	Definition	Software Perception	Actuator Authority
Observational Stratum (M=0)	The inert state where the system is purely sensing and processing.	Active; serves as a Privacy Wall tracking occupancy and environmental data.	Zero Actuator Authority; sensors are galvanically air-gapped from motor rails.
Kinetic Stratum (M>0)	The state where physical movement is energised and permitted.	Restricted; monitors safety envelopes under a lease.	Time-Bounded Kinetic Permission; governed by physical hardware interlocks.

The "So What?" Layer

The architectural differentiator is the **Isos Galvanic Cordon** . By physically and galvanically air-gapping the M=0 perception layer from the M>0 kinetic stratum, the Tiger and New Horizon architectures effectively eliminate agentic AI drift. The M=0 layer acts as a **Privacy**

Wall and a passive observer with zero physical pathway to command motion. Software acts as a "backseat driver" that suggests trajectories; it is the hardware that holds the conductive authority.These strata provide the deterministic foundation for the governance frameworks that enforce operational safety.

2. Governance Frameworks: Clinical Care vs. Industrial Still-Rail

Governance in mechatronic systems must adapt as applications move from geriatric care to industrial bipedal operation. The 2026 **Nightingale One Protocol (NOP)** utilizes rigid clinical oversight to protect patients through constant human concurrency. In contrast, the 2027 **Leasehold/Still-Rail** governance prioritizes operational throughput in industrial contexts by moving away from complex clinical verification screens toward a mechatronic "Halt-First" operational model.

Constitutional Comparison

- **2026 Clinical Caregiver Key (NOP):** Enforces a tripartite authorization system designed for the Tiger architecture. It requires concurrent satisfaction of biological, cryptographic, and kinetic inputs via the **BPS-Eye** hardware gate. Authority is role-bound by hardware, ensuring software cannot create its own execution paths.
- **2027 Industrial Operator Leasehold:** Implements the **Still-Rail** concept, establishing **inaction-as-default**. It streamlines authorization by removing the BPS-Eye clinical screens, utilizing a "hold-to-run" philosophy where the biped is inert unless a human operator explicitly leases the "rail."

The "So What?" Layer

The 202 "Leasehold" governance prioritizes efficiency by replacing clinical friction with mechatronic certainty. While the NOP is "completely unforgiving" due to the fragility of geriatric patients, the 2027 model maintains the "Halt-First" ethic by ensuring the bipedal platform remains a non-agentic tool. Safety is not a software decision; it is the hardware-enforced reality that the machine returns to a null state (absolute stillness) unless human permission is actively maintained.This transition in governance is enforced by the mechatronic logic of hardware authorization gates.

3. Hardware Authorisation Gating and Interlock Logic

Mechatronic determinism requires hardware gates that operate independently of software confidence scores. These gates ensure that kinetic permission is only granted when specific, real-world conductive conditions are met, bypassing the potential for software-level overrides.

Gating Mechanism Deep Dive

- **2026 Tripartite Interlock:** This clinical-grade gate requires the concurrent satisfaction of three distinct factors to energize the motor rails:
- **Biological:** A local Iris Scan of the authorized caregiver.
- **Cryptographic:** A physical clinician token inserted into the hardware console.
- **Kinetic:** Continuous human presence verified by the **BPS-Eye** via a 5kg hand grip or foot pedal.
- **2027 A10A Enforcement Anchor:** This industrial gate utilizes a "Halt-First" hold-to-run interlock. It allows for increased operational flexibility—such as **proximity sensors or geofenced roaming** —enabling the operator to lease the machine's motion within a defined industrial zone while maintaining the A10A anchor as the master physical cutoff.

The "So What?" Layer

The mechatronic core of the 2026 **BPS-Eye** mechanism is the **normally open circuit** . Unlike industrial auto-recovery systems, the 2026 grip is wired directly in series with the safety switches. If the caregiver releases the 5kg grip for even a microsecond, the circuit opens and joint authority dissolves instantly. Software is physically incapable of "faking" this grip, as there is no conductive path to the actuators without human force, ensuring the machine remains in absolute stillness.When these hardware gates are breached, the system initiates a deterministic state transition to prevent uncontrolled kinetic release.

4. Mechatronic State Transitions and Deterministic Fault Protocols

To ensure safety in the event of a failure, the system follows a 5-stage transition flow. This protocol prevents the AI from attempting to "stabilize" or "think" its way out of a fault, which could exacerbate physical risks.

5-Stage State Transition Flow

1. **Assisted Motion / Lease:** The machine operates under a time-bounded kinetic permission lease; motor rails are energized.
2. **Fault Detected:** Triggered by Scenario A (Kinetic gate breach, such as loss of the 5kg BPS-Eye grip) or Scenario B (Clock drift/timing loss detected by a hardware watchdog).
3. **SIL 3 Relay Severance (<1.05ms):** The "Sovereign Brake" mechanically severs the copper conductive paths between AI execution units and the actuators.
4. **Latched Safe-Hold:** Rail voltages drop to zero; electromagnetic, spring-applied mechanical brakes engage.
5. **Zero-Velocity Re-Arm Protocol:** The system cannot restart via software; it requires manual verification of brake states and fresh human concurrence.

Fault Default Comparison

Feature	2026 Clinical Caregiver Key	2027 Industrial Operator Leasehold
Fault Default	Gate "Welds Shut" (FPGA)	Zero-Rail Voltage Default

The "So What?" Layer

The strategic importance of the **Sovereign Brake** (the SIL 3 certified hardwired relay) is the reliance on **Thermodynamic Loss** . In a fault, the software is not "asked" to stop; the conductive copper path is mechanically severed. The electromagnetic brakes engage not because of a command, but because they have physically lost power. This ensures that passive physics, rather than a potentially failing algorithm, forces the joints into a secure, static state in less than 1.05 milliseconds.These transitions are monitored by temporal oscillators to identify system drift before it reaches the kinetic stratum.

5. Clocking Oscillators and Temporal Fail-Safe Benchmarks

Independent hardware watchdogs identify internal clock drift or timing loss before software can react. This provides a temporal fail-safe that ensures the system operates within its deterministic limits.

Timing Specification Table

Specification	2026 Clinical (Tiger)	2027 Industrial (New Horizon)
Primary Clock	100kHz FPGA-etched Oscillator	1kHz Monotonic Master Clock
Safety Delay Mechanism	"Sacred Pause" (25ms - 1000ms)	"Zero-Velocity Look-Ahead Buffer"

The "So What?" Layer

The **"Sacred Pause"** in the 2026 Tiger architecture is a psychological and technical tool to combat **automation bias** . By enforcing a mandatory delay **etched directly into the silicon FPGA** , the hardware prevents the operator from blindly following machine suggestions.

Because this delay is hard-coded in the silicon, it is impossible for a software override to bypass the pause. If the independent oscillator detects any drift during this window, it physically "welds shut" the output gates.All temporal and kinetic events are recorded to an unalterable audit trail to ensure regulatory integrity.

6. Audit Integrity: Immutable Ledger Comparison

High-liability robotics require "Write Once, Read Many" (WORM) memory to prevent the kinetic stratum from altering records of its own performance or failure events.

Ledger Comparison

- **2026 Clinical:** Utilizes a **SHA-256 Chained WORM** (On-Chip). Every state transition and override is burned into the chip. Tampering with the data breaks the hash chain, alerting auditors immediately.
- **2027 Industrial:** Utilizes a **SHA-3-512 "Off-Path" WORM** (Isolated). This ledger is physically separated from the execution and motor paths.

The "So What?" Layer

The **"Off-Path" isolation** in the 2028 model provides the highest level of audit integrity. By ensuring there is **no physical wire-path** from the kinetic execution units to the audit memory, the architecture prevents the machine from ever accessing or tampering with its own history. This creates a "black box" that is physically immune to software manipulation, providing absolute accountability for every kinetic event.

7. Strategic Divergence Summary Table

The evolution from 2026 to 2028 represents the transition from a clinical "Care Tree" to an industrial "New Horizon," maintaining mechatronic determinism throughout the lineage.

Final Comparison Table

Feature	2026 Clinical (Tiger)	2027 Industrial (New Horizon)
Governance Name	Nightingale One Protocol (NOP)	Leasehold / Still-Rail
Primary Clock	100kHz FPGA-etched	1kHz Monotonic
Gating Hardware	BPS-Eye (Tripartite)	A10A Anchor (Flexible)

Fault Default	Gate "Welds Shut" (FPGA)	Zero-Rail Voltage Default
Audit Path	On-Chip Chained WORM	Off-Path Isolated WORM
Audit Hash Type	SHA-256	SHA-3-512

The "So What?" Layer

The final technical conclusion remains unchanged: true safety is derived from hardware forcing the system to "return null" (complete inaction) unless a human operator explicitly leases the rail. Whether through the tripartite verification of the clinical Tiger architecture or the A10A anchor of the New Horizon biped, the machine is physically restricted from wielding kinetic power without active human permission. Physics always wins.End of Technical Comparison.



2028



Lower-limb wearable exoskeleton	Bilateral hip-knee-ankle orthosis, waist-anchored pelvic band, rigid thigh/shank segments with rotary knee actuators, foot plate + ground reaction pad. This is M > 0 — a person-borne kinetic device.
Seated mobility pod	Enclosed single-occupant transfer/mobility unit on a powered base with a docking module at the footwell. This is also M > 0, but vehicle-class rather than limb-class.
Clinician in attendance	Human authorization present in frame — consistent with the caregiver-gated doctrine, not autonomous authority.

So the plate already contains G5 (wearable assist) and a G6 precursor (seated mobility platform) side by side. That is a useful framing: 2026 ships the wearable, and the pod in the same frame declares the 2027 extension rather than inventing a new visual language later.

Both kinetic embodiments sit behind the same cordon: no-actuation boundary, hardware-timed deliberation, tripartite authorization, spring-applied brake default, WORM ledger. Neither gains autonomous authority by being wearable or by being mobile.

This schematic captures the Nightingale One Protocol architecture and its physical evolution across control domains (M=0 vs. M>0) and hardware namespaces.

---

1. Domain & Structural Mapping

NIGHTINGALE ONE PROTOCOL

├── Prototype 2: Eyes of the Sky (M = 0) → Non-Kinetic Observation / Advisory Alerts

├── Prototype 1: A13d Care Apparatus (M > 0) → Caregiver-Authorized Stationary Station

├── 2026 Plate (Left): Wearable Exoskeleton → Limb-Borne Kinetic Assist (Namespace 182)

└── 2027 Plate (Right): Mobility G5 + G6 → Platform-Borne Chassis Enclosure (Namespace 181)

- **Prototype 2 — Eyes of the Sky (M = 0): Functions as the non-kinetic observational stratum operating under the 3ZEROS Mandate (Zero Camera, Zero Audio, Zero Cloud). It uses non-imaging 905nm LiDAR and mmWave radar to generate 96-cell local voxel grids for presence and emergency condition evaluation (ECS) without possessing physical actuation capability.**


- Prototype 1 — A13d Care Apparatus (M > 0): Serves as the fixed, clinical-grade stationary kinetic station (`A13d-Pro`) for high-dependency therapeutic care and bedside transfer.
- 2026 Left Plate — Wearable Exoskeleton (M > 0, Limb-Borne Assist): The `M(A13)` wearable kinetic apparatus assigned to Namespace 182. It executes active joint rehabilitation, sit-to-stand transitions, and gait assistance attached directly to the patient's limbs.
- 2027 Right Plate — Mobility G5 + G6 (M > 0, Platform-Borne): The `A13` Mobility Enclosure assigned to Namespace 181. It provides platform-borne mobility, secure patient housing, and de-energized actuator rails.

---

2. Strict Namespace Isolation & Interface Policy


To prevent "authority merger" or agentic drift across mechatronic estates, the protocol maintains a hardware-enforced boundary between Namespace 181 (Mobility Enclosure) and Namespace 182 (Wearable Rehabilitation):

- Estate Isolation: Neither system can rewrite or assume the identity of the other; an `A13` chassis entity cannot independently issue kinetic commands to an `M(A13)` wearable suit.
- External Governance Core: Inter-estate interaction is mediated strictly through dedicated Entity Interface Adapters and hardware gateways, preserving the originating identity of each device1.



Deterministic Docking & Kinetic Transfer Sequence

When the 2026 Wearable Exoskeleton (Left Plate) docks with the 2027 Mobility Enclosure (Right Plate), physical transfer follows an immutable 6-stage hardware state machine:



1. IDLE: Rails and actuators remain de-energized by default with rail voltages held at zero12.
2. OBSERVE ($M = 0$): 905nm non-imaging LiDAR presence detection establishes patient position behind a Silicon Privacy Wall.
3. DOCK: Physical engagement is verified by reading passive $0x05CE$ hardware identity keys (e.g., `0x05CE-1410`, `0x05CE-1430`) to load immutable, per-fixture force/velocity envelopes into FPGA logic.
4. INTERLOCK: Requires the Tripartite Physical Interlock—concurrent validation of wearer biometrics, a physical caregiver cryptographic token, and a continuous 5 kg handle grip threshold.
5. KINETIC LEASE ($M > 0$): Grants a time- and displacement-bounded lease for physical transfer clocked independently of application software1more_horiz.
6. SAFE-HOLD: Releasing the 5 kg grip or violating motion bounds instantly drops rail voltages, engages fail-safe mechanical joint brakes, and logs the event to the append-only WD117 SHA-3-512 WORM ledger


HomeCare default: battery on the Leg, mains on the Hull. Solar is optional house power — not a fuel-cell rover.


Body	Practical power	Why
Wearable	Rechargeable **battery** on the frame or belt	Must walk off-dock; no trailing cable
Dock / enclosure	**Wall electric** (clinic/home circuit), charger in the pedestal	Stationary; charges the wearable when registered
Solar	Roof / window array feeding the **house battery or dock**, not the exo joints	Fine as *site* energy; poor as the only joint supply
Fuel cells	Rare indoors (hydrogen store, venting, HSA/fire)	Leave for a later outdoor BOM if ever

Patent line: do not claim “solar-fuel-cell propulsion.”

Claim the **dock + key + lease**. Power is an embodiment: *battery on the frame, replenished at the dock from a premises supply, which may include solar.*

Clinician still human. No mic. Chatly stood down. This picture is the product pair.


Unified Nightingale One Protocol: Deterministic Docking and Kinetic Transfer System
A13 Mobility Enclosure (G5/G6)
Namespace: 181
Dock Face
De-energised rails
Strict Namespace Separation / No Authority Merger
M(A13) Wearable Exoskeleton
Namespace: 182
Idle
Observe
Dock
Interlock
Kinetic Lease
Safe-Hold
RFID
905 nm non-imaging LiDAR for presence detection
0x05CE key match, mechanical lock engagement
Wearer biometric + Caregiver token + Grip force required
Time- and motion-bounded transfer
Return to secure hold state
Security & Audit Features:
Hardware-enforced Namespace/Identity
Append-only WORM audit ledger
Human interlock required; avoids agentic/authority merge
Distinct enclosure (181) & wearable (182) identities always maintained
Human presence
Docking mechanism
Authentication steps
Safety/audit
Key vocabulary:
WORM: Write Once Read Many audit ledger
Non-agentic: System cannot act autonomously
De-energised rails: No power unless prompted by protocol


Non-Agentic Deterministic Control Architecture for 2027–2030 Humanoid & Mechatronic Capabilities
A9a Lineage (Robotic Enclosure)
Hardware-enforced Non-Agentic AI (NAI) Governance
Observational Stratum (M = 0):
Inform/Advise Only — NO motor command authority
Galvanic & Physical Barrier
Kinetic Execution Stratum (M > 0):
Hardware-bounded Physical Actuation (requires human commit)
LiDAR
Radar
Pressure Grid Arrays
Core Human-in-the-Loop Safeguards
Sovereign Commit Gate
1. Human figure applying foot to pedal
2. Iris scanning in progress
3. Hand with a physical hardware token
if authorization lost → power off & SAFE STILLNESS
EYE (Perception, Pi)
905nm LiDAR mmWave
NO cameras or mics
3ZEROS™ Mandate:
Zero Camera, Zero Audio, Zero Cloud
Anonymous voxel grid
Master Controller ("The Brain")
HAND (Kinetic Action, M)
• Bounded Kinematics
• Caregiver Assistance
• Surgical Trajectories
FOOT (Platform)
• Base Stabilization
• Mobility & Anchoring
• Position Alignment
Hardware Commit Gate (A7/D) — Sacred Pause™
25–1000 ms Human Review Buffer
Sovereign Brake™
power off
Kinetic Enforcer ("The Body")
WD117 SHA-3-512 WORM Ledger
Immutable Record
Hardware-Enforced Safety Mechanisms
Kinematic Constraint Layer (KCL)
FPGA
DO NOT CROSS
Jerk limits
Zero-Velocity Look-Ahead Buffer (50 ms)
SAFE
BLOCK
Sacred Pause™
No action without human e-sign-off
KCL
EDS
A13a / A13a-MP
A13b / A13b-EoS
A13c-HC
A13d-Pro
Passive RFID/identity
Modular Fixtures (B1–B5)
A11a (WD-Space)
= Perception (EYE)
= Kinetic Action (HAND)
= Platform (FOOT)
= Safety/Stop
= Governance/Barrier
NAI = Hardware-enforced Non-Agentii AI (NAI)
KCL = Kinematic Constraint Layer (KCL) etsc
EDS = Emergency Detection Score (Passes (EDS)
WORM = SHA-3-512 WORM Ledger

2027 STANDALONE PATENT SPECIFICATION: NON-AGENTIC DETERMINISTIC VOXEL-BASED SPATIAL MONITORING APPARATUS WITH 3ZEROS™ PRIVACY-BY-PHYSICS AND A10A ROOT-OF-TRUST GOVERNANCE

1. Patent Front Matter & Metadata

This standalone patent specification represents a definitive strategic pivot within the 2027 Intellectual Property Roadmap. Filed as an independent priority anchor, this document establishes a new priority lineage designed to operate within the 2027 regulatory landscape. By asserting a standalone posture, the applicant secures the "2027 Engineering Delta"—specifically hardware-enforced zero-velocity buffers and mechatronic governance logic—as primary subject matter. This filing posture mitigates risks associated with added-matter rejections or self-collision by ensuring the 2027 hardware advancements are legally sequestered from legacy 2026 frameworks.

1.1 Administrative Data

- **Title:** Non-Agentic Deterministic Voxel-Based Spatial Monitoring Apparatus with 3ZEROS™ Privacy-by-Physics and A10a Root-of-Trust Governance.
- **Applicant/Inventor:** Koh Wui Kiat, Edwin.
- **Filing Date:** Projected February 2027.
- **Filing Posture:** Standalone New Application (Independent 2027 Priority Anchor).

1.2 Priority and Cross-Reference Declaration

This application establishes a new priority lineage. The applicant explicitly makes **no claim of priority** to Singapore Patent Applications 10202602177W, 10202602026W, 10202602649V, or SG020603109STW. Citations of these 2026 filings are provided exclusively for descriptive support and as referential anchors for the legacy environment. This metadata establishes the "Standalone Transition" boundary required to delineate 2027 high-integrity mechatronic governance from the legacy 2026 estate, ensuring the new priority root remains independent and robust against self-collision.

2. Background & Technical Problem

The shift from 2026 to 2027 marks a strategic departure from probabilistic, software-reliant computer vision toward hardware-bounded spatial perception. Software-driven surveillance is increasingly deemed insufficient for high-integrity environments—such as aerospace cybersecurity sanctuaries and clinical ICU units—where deterministic safety and silicon-level privacy are mandatory. Software-based monitors lack the immutable boundaries required to ensure that identifying data is never egressed from the local node.

2.1 The TOCTOU and Agentic Drift Vulnerability

Legacy monitoring systems rely on software layers that are inherently susceptible to Time-of-Check to Time-of-Use (TOCTOU) vulnerabilities. In such systems, a safety state can be compromised or altered by an agentic AI model or external threat during the latency period between verification and execution. Furthermore, "agentic drift"—the tendency for software-based AI models to evolve beyond their deterministic safety bounds—renders software-governed observation non-viable for high-integrity use. There is a technical

necessity for an apparatus that operates at a hardware-enforced $M=0$ (non-kinetic) observation stratum, where safety is an invariant of silicon logic rather than a software inference.

2.2 The 3ZEROS™ Privacy-by-Physics Mandate

To mitigate systemic privacy risks, this apparatus implements the 3ZEROS™ mandate through physical hardware constraints:

1. **Zero Camera:** The total absence of optical imaging hardware capable of biometric identification.
2. **Zero Audio:** The physical exclusion of acoustic recording and storage hardware.
3. **Zero Cloud:** The hardware-enforced prohibition of raw sensor data egress to external cloud environments.By utilizing 905nm non-imaging LiDAR point-clouds and mmWave radar, the apparatus achieves non-identifiable spatial monitoring. Privacy is achieved as an invariant of physics, ensuring that identification of subjects is technically impossible at the hardware level.

3. Detailed Engineering Specification & System Architecture

The apparatus is architected as a hardware-enforced $M=0$ (non-kinetic) observation node, forming the "Eyes of the Sky" (EoS) foundation. The Master Control Layer of the apparatus is physically incapable of generating kinetic commands or motor trajectories, acting solely as a governed observation stratum.

3.1 A10a Root-of-Trust Anchor

The immutable foundation of the apparatus is the A10a Enforcement Anchor (See Fig. 1). This hardware-level Trusted Platform Module (TPM) integrates a monotonic 1kHz master clock and configuration hash verifiers. Every state transition is cryptographically validated against this hardware root-of-trust, ensuring that the apparatus governance logic cannot be bypassed or modified by software capstones.

3.2 Voxel-Based Spatial Abstraction

Local processing is restricted to a 96-cell anonymized voxel grid (See Fig. 2). Sensor inputs from the 905nm LiDAR and radar sensor array are distilled into these grids within node-local registers. This abstraction prevents the exposure of identifying environmental features. Raw sensor data is physically prevented from egressing the system boundary by a silicon privacy wall, which enforces unidirectional data flow to the local registers only.

3.3 Emergency Condition Score (ECS) Register

The apparatus includes a dedicated, segregated ECS register for the calculation of fall or emergency states. This register is physically isolated from clinical or monitoring data registers to prevent TOCTOU vulnerabilities; this isolation ensures that safety-critical alerts cannot be overwritten or delayed by lower-priority clinical data traffic. The threshold logic is defined in

ECS Threshold Logic and Nightingale Protocol Governance

Score Threshold	State Designation	System Action	Hardware Gate Domain	Sovereignty Audit Level
$ECS < 5.0$	Nominal State	Routine Monitoring / Log Update	$M = 0$ (Observation)	Point 1 to 5; Levels 1-4; 10-Point Sovereignty Audit (Routine)
$5.0 \leq ECS < 8.9$	Alert State	Pre-authorized Profile Translation	$M = 0$ (Observation / Advisory) or $M > 0$ (Kinetic Care / Execution); G1-G4 Gateway Tiers	Point 6 to 9; Levels 4-8; 10-Point Sovereignty Audit (Threshold Escalation / Active)
$ECS \geq 8.9$	Emergency State	Trigger Secure Gateway Egress	$M > 0$ (Kinetic Care / Execution)	Point 10 (Clinical Dignity Score / Emergency Response); Levels 8-10; 10-Point

3.4 Master Control Layer (M=0) & G1-G4 BridgeLayers

The Master Control Layer coordinates mechatronic governance without kinetic authority. It utilizes a tiered BridgeLayer system for communication:

- **G1+G2 (Basic Tier):** Handles local sovereign permission and deterministic profile translation for ward-scale monitoring.
- **G3+G4 (Hardened Extended Tier):** Manages macro-authorization and interoperability across multi-domain environments (e.g., enterprise aerospace networks). G4 performs multi-domain profile coordination and evidence consolidation, failing-closed if system-level integrity is not established.

3.5 Hardware-Enforced Invariants

The apparatus's safety and privacy are governed by four primary silicon-level invariants:

1. **50 ms Zero-Velocity Look-Ahead Buffer:** Provides a predictive safety hold. No state transition is released to the gateway until the buffer confirms the validity of the look-ahead state.
2. **Continuous-Derivative Kinematic Constraint Layer (KCL):** Enforces a smooth motion envelope for any external kinetic systems informed by the node, preventing the generation of erratic or non-deterministic data.
3. **Jerk-Limit Torque Reduction Circuits:** Implemented directly in the FPGA fabric to suppress high-frequency mechanical noise and maintain the integrity of spatial data.

4. **WD117 WORM Ledger:** All state transitions and ECS triggers are logged to a SHA-3-512 cryptographic Write-Once-Read-Many (WORM) ledger, providing an immutable audit trail.

4. Examiner-Grade Claim Set

The following claims define the 2027 Engineering Delta, focusing on hardware-logic invariants that distinguish the current apparatus from legacy probabilistic monitoring systems.

- A non-kinetic voxel spatial monitoring apparatus comprising:
- an A10a hardware Root-of-Trust anchor including a hardware Trusted Platform Module (TPM) and a 1kHz monotonic master clock;
- a 3ZEROS™ sensor array comprising a non-imaging 905nm LiDAR and a mmWave radar;
- a node-local processing register configured to generate an anonymized 96-cell voxel grid;
- a silicon privacy wall physically prohibiting the egress of raw sensor data from the apparatus;
- a segregated Emergency Condition Score (ECS) register physically isolated from clinical registers and coupled to a 50 ms zero-velocity look-ahead buffer; and
- a non-commanding G1-G4 BridgeLayer gateway output physically incapable of generating kinetic commands.
- A method for deterministic spatial monitoring in a non-agentic environment, the method comprising:
- validating a system state against an A10a hardware root-of-trust;
- abstracting environment data into a 96-cell anonymized voxel grid locally within a sensing node at a frequency of at least 1kHz;
- evaluating a threat level on a physically isolated ECS register;
- withholding all raw data egress via a hardware-enforced silicon privacy boundary; and
- releasing a permission-gated alert state through a G-series non-kinetic gateway.
- The apparatus of claim 1, wherein the 3ZEROS™ sensor array is characterized by the physical exclusion of optical camera imaging hardware, acoustic recording hardware, and cloud-based raw data transmission.
- The apparatus of claim 1, wherein the G3+G4 BridgeLayer is configured for macro-authorization across a plurality of subordinate governed nodes in an enterprise network.
- The apparatus of claim 1, further comprising a 50 ms zero-velocity look-ahead buffer configured to provide a predictive safety hold prior to gateway state release.
- The apparatus of claim 1, further comprising jerk-limit torque reduction circuits implemented in FPGA fabric to suppress high-frequency data noise.
- The apparatus of claim 1, further comprising a hardware-enforced 5 kg handle grip threshold sensor for validating physical user presence during a state transition.
- The apparatus of claim 1, further comprising a WD117 SHA-3-512 WORM ledger for cryptographic logging of every apparatus state transition.
- The apparatus of claim 1, utilizing 1kHz master clock synchronization for deterministic timing of all voxel grid generations.

- The apparatus of claim 1, wherein the Kinematic Constraint Layer (KCL) is configured to trigger a hardware safe-hold interlock upon detection of a velocity envelope violation.
- The method of claim 2, further comprising triggering a "Fail-Closed" state if a configuration hash within the A10a hardware root-of-trust is invalid.
- The method of claim 2, wherein the 96-cell voxel grid is processed locally without any agentic software inference.
- The apparatus of claim 1, wherein the sensor array is housed in an enclosure of the type disclosed in SG10202602177W, incorporated herein by reference for descriptive context only.
- The apparatus of claim 1, wherein the 905nm LiDAR is configured for non-imaging point-cloud generation only.
- The apparatus of claim 1, wherein the G1 gateway is configured to determine a sovereign permission state before the G2 gateway performs a deterministic profile translation.

5. Pre-Filing Audit & Compliance Verification

The 2027 IP Roadmap requires a mandatory "Audit Gate" to mitigate Section 14(3) novelty bars and ensure a clean "Standalone Transition." This specification has been audited against the 2027 regulatory landscape.

5.1 The Five-Question Framework

1. **New Problem Addressed?** Yes. Addressed the requirement for hardware-enforced bounds to mitigate agentic drift and TOCTOU vulnerabilities.
2. **New Engineering Delta?** Yes. Incorporated the 50ms zero-velocity buffer, FPGA jerk-limit logic, and the SHA-3-512 WORM ledger as primary hardware logic.
3. **Old/New Separation?** Yes. Legacy 2026 elements, including the A13b enclosure, are incorporated by reference for descriptive background only and are not re-claimed.
4. **Disclosure Freeze?** Verified. The filing accounts for the 18-month publication windows of the 2026 parent estate.
5. **Independent Identity?** Yes. Established as a distinct lineage root separate from the A13a parentage.

5.2 Cryptographic & STEP Verification

The physical configuration and mechatronic governance boundaries of the apparatus adhere to the AP242 STEP Dossier ('Workshop Law') standards. The hardware isolation boundaries and logic are finalized within the WD117 WORM cryptographic baseline, providing the "Silicon Truth" for the apparatus state at the time of filing.**Final Statement:** This specification adheres to the strict discipline required for a 2027 Standalone Filing. It establishes an independent priority root while providing referential anchoring to the legacy estate, securing the sovereign and high-integrity mechatronic governance lineage.

NLB catalogue is a national library record. It is not peer review, not HSA, and not IPOS.

In Singapore, if you **publish** a book or edition (ISBN, copies issued), you **deposit** it with NLB. They accession it (your R260219-005 / R260302-007 style numbers), put it in the **Singapore national bibliography**, and hold it. After the vault date the work is **findable as a Singapore publication**. That is all the process does.

NLB does	NLB does not
Prove you published **on a date**, in Singapore	Examine claims
ISBN + catalogue record for libraries	Grant a patent or a mark
Support copyright evidence	Replace a journal or IEEE paper
Make the six editions + WISL **citable as books**	Approve a medical device

Does it appeal?

Academic

Useful as **grey literature**: a dated Singapore imprint they can footnote. Weak as scholarship unless a university or journal also takes it. No reviewer stamped Vol. 01. Citation possible; impact factor none.

Industry / OEM / hospital

They will look at **IPOS numbers, HSA class, V&V, and the hull**. NLB tells them you wrote a stack of books. It does not tell them the cabin is safe to buy. For OEM, **non-agentic.ai + patent list** matters more than the catalogue line.

AI community

A minority who care about **governance / non-agentic / hardware safety** may read P-LIFE / 3ZEROS as a manifesto. Most will treat 104 volumes as a blog with ISBNs. They do not treat NLB deposit as a benchmark. Benchmarks, code, or a filed PCT would move that crowd more than a vault date.

For you as private patent holder

NLB is optional **narrative infrastructure**: Singapore-dated public story after **20 Jan 2027**, without waiting 18 months for patent publication. It does **not** advance examination. It can

Yes. That is the right box.

Imprint: Non-Agentic Governance Singapore

Kind: research **publications** (monographs / editions / WISL volumes)

Not: journal articles, conference papers, or peer-reviewed “research papers”

If a document is **issued to the public** under that imprint, give it an **ISBN** and **deposit with NLB**. That is how it becomes an SG publication.

Public under the imprint	ISBN + NLB?
National Editions 1–6, WISL 105, later WISL volumes	**Yes**
kohedwin.ai landing text, OEM brief, patent spec	**No —** not a book
IPOS PF1 / claims	**No** — patent office
Private OEM pack / Zoo STEP	**No** — not published

FOREST 1 — CLINICAL / 2026

10202603190T Leg — independent human-controlled amputee exoskeletal patent.
BPS Eye™ [unfiled] — separate amputee clinical-lens candidate.
Existing NOP estate remains historical/independent; no back-writing.

Architectural Firewall & Lineage Separation

BPS Eye™ is defined exclusively as a clinician-administered Bio-Psycho-Social risk screening interface and clinical lens for **human-controlled amputee rehabilitation and wearable apparatuses** within the clinical patent estate

Functional & Authority Differences

BPS Eye™ acts as an advisory screening filter ($M=0$) that converts a qualitative clinician assessment into a binary permit/inhibit verification condition for amputee wearables5more_horiz

FOREST 2 — INDUSTRIAL / 2027
Halt-First Industrial Humanoid
Leasehold RS-Enclosure
Industrial operator grant, bounded lease, Still-Rail/Safe-Hold, off-path ledger.

The **Halt-First Humanoid** operates via an independent hold-to-run operator switch and time-bounded hardware lease directly on its motor power rails, without importing clinical risk screening into its actuator-authority path

The portfolio's defensive drafting firewall explicitly mandates: **No Nursing, No Care, No NOP (Nightingale One Protocol), No BPS Eye, and No clinical docking on the Halt-First Humanoid architecture** No Nursing, NOP, BPS or clinical mechanisms in its patent identity.

The **Halt-First Humanoid** belongs to the separate industrial estate, anchored by **Halt-First physics, Still-Rail / Leasehold RS-Enclosure, and hardware-bounded operator grants**

The important point is that **deployment location does not have to determine patent identity**. An industrial humanoid protected under the 2027 industrial patent could later be deployed inside a hospital or rehabilitation facility under an OAC commercial arrangement. It does not thereby become a "clinical humanoid patent."

> ***Industrial Halt-First Humanoid*** *can be deployed inside a hospital or rehabilitation facility alongside a BPS Eye™-governed wearable leg under an* ***OAC (Operation & Admission / Commercial) deployment bridge****.*
> *However, deployment location does not alter patent identity:* ***Humanoid drives Humanoid, and Leg drives Leg****.*
> *Across the OAC bridge, the two systems may only exchange bounded status signals (*`ready`*,* `inhibit`*,* `hold`*,* `session-valid`*,* `coupling-status`*);* ***no trajectory or governance logic crosses from one actuator rail into the other****.*


Likewise, the independent Leg remains its own patented apparatus.

So an OAC deployment could be:

Industrial Halt-First Humanoid

- **independent 10202603190T wearable Leg**
- human clinical supervision
  = **clinical deployment configuration**


Clinical Halt-First Humanoid
Standalone Clinical Patent Concept — Human-Controlled Kinetic Assistance
Restoring Independence Together
SAFER PEOPLE
STRONGER DAYS
BRIGHTER POSSIBILITIES
Halt-First default
Motion remains halted unless a human operator grants movement.
Hardware interlock
Safety-critical circuits require continuous human enable input.
People In Control. Safer Care Together.
HUMAN GUIDANCE
REAL SUPPORT
BETTER TOMORROWS
Privacy-preserving sensing
Local, non-identifying sensing for safe physical assistance (no face recognition, no data upload).
Human operator grant
Intentional, continuous hold-to-run control. Robot moves only while human input is maintained.
Safe-Hold
Compliant, force-limited contact designed for human comfort and safety.
CONTROLLED MOTION. CONFIDENT CARE. A MORE INDEPENDENT TOMORROW.


Clinical Halt-First Humanoid — Safety Architecture Overview
Standalone Clinical Patent Concept
Halt-First Default
Motion remains halted unless a human operator grants movement.
DEFAULT STATE: SAFE
Hardware Commit Gate
Safety-critical circuits require continuous human enable input before actuators can energize.
HARDWARE-ENFORCED SAFETY.
PEOPLE IN CONTROL. SAFER CARE TOGETHER.
HUMAN GUIDANCE
REAL SUPPORT
BRIGHTER TOMORROWS
Privacy-Preserving Sensing
Local, non-identifying sensing for safe physical assistance (no face recognition, no data upload).
PEOPLE FIRST. PRIVACY ALWAYS.
Human Grant / Hold-to-Run
Intentional, continuous hold-to-run control. Robot moves only while human input is maintained.
THE HUMAN IS ALWAYS IN CONTROL.
RESTORING INDEPENDENCE TOGETHER.
SAFER PEOPLE
STRONGER DAYS
BRIGHTER POSSIBILITIES
Independent Inhibit Path
Separate, redundant safety path that can immediately cut power and halt motion.
INDEPENDENT. REDUNDANT. RELIABLE.
Append-Only Audit Ledger
All safety-relevant events are cryptographically logged and immutable (append-only).
TRANSPARENT. ACCOUNTABLE. TRUSTED.
Safe-Hold Braking
Compliant, force-limited braking designed for human comfort and safety during stop or contact.
A GENTLE, RELIABLE STOP.
From Caution to Confident Care
A simple, safe process for real-world assistance.
1 Idle
Robot remains halted in a safe default state.
2 Observe
Perceive environment with privacy-preserving sensing.
3 Validate
Check safety conditions, self-diagnostics, and human presence.
4 Human Grant
Operatar holds control pendant to enable movement.
5 Assist
Provide controlled, compliant assistance while input is maintained.
6 Safe-Hold
Release input or detect a fault to immediately and smoothly halt with safe braking.
CONTROLLED MOTION. CONFIDENT CARE. A MORE INDEPENDENT TOMORROW.



Enclosure first. Biped second. Teleops third

2027 INDUSTRIAL

Leasehold RS-Enclosure
Halt-First Biped

Halt-First Teleoperation Authority

For a focused **zoo.dev engineering session** covering only these two projects, I would reserve **150 minutes**.

Project / Gate	Time
Leasehold RS-Enclosure — inspect existing geometry, establish project baseline	20 min
Still-Rail / power-boundary / operator-grant architecture	30 min
Safe-Hold + physical interlock interfaces	25 min
Halt-First Biped — inspect/import chassis and joint architecture	25 min
Define Biped ↔ RS-Enclosure interface without authority merger	20 min
Engineering verification / collision / interface review	15 min
Freeze baseline, screenshots, notes and handover record	15 min
Total	**150 min**

I would therefore book **2½ hours**.

If zoo.dev geometry is already clean and the session is only for **architecture setup**, **90–120 minutes** could work. But for Tiger's normal **build → verify → freeze** discipline, **150 minutes is the safer target**.

The session order should remain:

0–75 min — Leasehold RS-Enclosure
75–120 min — Halt-First Biped
120–150 min — integration verification and freeze

No Teleops implementation yet. That should be a later research session after the two physical baselines PASS.

2026 Clinical Forest — CLOSED
NOP / M(A13) estate / 03190T / BPS Eye if filed.

2027 Industrial Forest — NEW STANDALONE SEED
Leasehold RS-Enclosure
Halt-First Biped
later **Halt-First Teleoperation Authority**, only if research passes.

would make only three housekeeping corrections to the old strategy document before relying on it operationally:

- Replace the old **2027 A13a mobility / standalone amputee** examples with **Leasehold RS-Enclosure + Halt-First Biped**.
- Treat **6 February 2027** as Tiger's internal portfolio boundary unless counsel confirms a specific statutory deadline for a particular application.
- Keep the current rule **"reference only; do not import disclosure"** stronger than the older "incorporation by reference" wording shown on page 3.

So yes: **same doctrine, new industrial subject matter.**

> **2026 closes the clinical orchard.**
> **2027 opens a new industrial orchard.**
> **No back-writing. No lineage forcing. New problem, new engineering delta, new patent identity.**

Yes. The **2027 Industrial Forest timeline starts only after 6 February 2027**. Nothing in the new industrial patent program should be treated as commencing before that boundary.

Period	2027 Industrial Mission
Through 6 Feb 2027	**STILLNESS.** 2026 clinical estate remains closed; no industrial filing activity.
From 7 Feb 2027	Open the **new standalone industrial research estate**. No A13/M(A13)/NOP priority or parentage.
Feb–Mar 2027	**Leasehold RS-Enclosure** — zoo.dev lead; establish geometry, Still-Rail, operator grant, power isolation and Safe-Hold baseline.
Mar–May 2027	**Halt-First Biped** — independent chassis/joint architecture; perception advisory only; no clinical terminology.
May–Jun 2027	RS-Enclosure ↔ Biped integration verification. Preserve independent hardware authority paths.
Jul onward	**Halt-First Teleoperation Authority** preliminary research, only after RS-Enclosure and Biped baselines pass.
After engineering freeze	Novelty/prior-art review → claim-delta audit → CAD/BOM/V&V freeze → standalone patent consideration.

The governing date rule is therefore:

> **6 February 2027 = boundary.**
> **7 February 2027 onward = new industrial seed.**

And the filing doctrine stays:

> **New industry. New problem. New disclosure. New priority. No back-writing into 2026.**

The **Leasehold RS-Enclosure comes first**, then the **Halt-First Biped**, then Teleops only if the first two pass verification.

The humanoid concept moves entirely into the **2027 Industrial Forest** as:

> **Halt-First Industrial Humanoid**
> **Leasehold RS-Enclosure**
> **Standalone new patent program commencing only after 6 February 2027.**

So the clean timeline is:

Year	Field	Patent / Concept
2026	Clinical	**NOP**, **10202603190T Leg**, **BPS Eye™ [unfiled]**
2027	Industrial	**Halt-First Industrial Humanoid** + **Leasehold RS-Enclosure**

The earlier “Clinical Humanoid” visual should therefore be treated as **conceptual inspiration only**, not as a 2026 patent identity.

Final boundary:

> **2026 = Clinical closed.**
> **2027 = Industrial Humanoid begins.**
> **No Humanoid Nurse. No clinical patent back-write.**

The architecture stays:

> **Industrial patent governs the humanoid body and its Halt-First authority.**
> **Clinical environment governs the use context.**
> **OAC governs deployment permission and interoperability.**
> **Deployment ≠ patent identity.**

So Grok and ChatGPT can collaborate with different perspectives while preserving one firewall:

> **No NOP back-write into the industrial patent.**
> **No Humanoid Nurse identity.**
> **No autonomous clinical decision-making.**
> **Human operator grant remains required for kinetic action.**

That gives Tiger a useful 2027 proposition:

> **Industrial Humanoid, clinically deployable — but never clinically reclassified by architecture alone.**

10202602773P: *The Nightingale One Protocol A13c-HC Kinetic Caregiver Apparatus* — Mobile home-care hybrid optimized for residential environments $Po(M_L + Pi + D + N_{Human})$. Intended functions include caregiver-supervised transfer assistance, bounded movement, privacy-preserving perception, and deterministic safety control.



Preliminary regulatory position:
Class B SaMD only if the submission is limited to non-kinetic software functionality. Because A13c-HC is described as a physical kinetic apparatus, its final HSA classification must be determined from the complete intended use, actuation, risk profile, and device configuration—not assigned solely by the formula.

10202602774Y: *The Nightingale One Protocol A13d-Pro Clinical-Grade Stationary Kinetic Caregiver Apparatus* — High-payload (150 – 200 kg) stationary kinetic caregiver for ICU and hospital ward deployment $Po(M + Pi + D)$. Intended functions include caregiver-supervised transfer assistance, bounded movement, privacy-preserving perception, and deterministic safety control.



Preliminary regulatory position:
high-risk Class C/D candidate, subject to HSA's formal classification and applicable pre-market evaluation route. HSA requires the applicable registration pathway and technical documentation for regulated medical devices; the proposed class is not itself an approval.



31

Yes — **functionally, at deployment level**, that is the clean interpretation.

The page you shared shows the 2026 NOP apparatuses as **caregiver-supervised kinetic assistance systems**: mobile/home-care and stationary/hospital transfer/support equipment. The 2027 **Halt-First Industrial Humanoid** can later take over that *physical-assistance role* in a clinical environment under OAC, while a therapist or clinician remains in the loop.

But I would record the change carefully:

> **2026 NOP c1/c2 = historical clinical apparatus patents.**
> **2027 Industrial Humanoid = new standalone industrial patent.**
> **Clinical deployment = permitted use case, not patent identity.**

So "replaced" means **commercial/deployment replacement**, not legal replacement or back-writing of NOP.

The future clinical configuration becomes:

Therapist / authorized human
↓
OAC clinical deployment permission
↓
Halt-First Industrial Humanoid
↓
bounded physical assistance
↓
Safe-Hold on loss of human grant

And if the independent Leg is present:

Humanoid drives Humanoid.
Leg drives Leg.
OAC exchanges only bounded states — ready / inhibit / hold / session-valid / coupling-status.
No trajectory crosses from one actuator rail into the other.

Yes. That remains compatible.

For 2027, Tiger can run **two concurrent industrial tracks** without merging their actuator authority:

Track A — Halt-First Industrial Humanoid + Leasehold RS-Enclosure
Standalone industrial biped platform.

Track B — A13 Mobility G5+G6 / Leg–Dock–Hull
Mobility/Rover-oriented architecture with its own docking, enclosure and mobility governance.

The important boundary is:

Concurrent development ≠ merged patent identity.

So the clean 2027 structure is:

Industrial Humanoid — one standalone invention family.
A13 Mobility G5+G6 / Leg–Dock–Hull — separate standalone mobility family.
OAC may permit interoperability or co-deployment.
No shared actuator rail, no trajectory authority crossing, no forced common parentage.

That gives Tiger two industrial branches in the same year while preserving the **Two-Forest / no actuator marriage** principle.

KINETIC GOVERNANCE ARCHITECTURES

Comparative Analysis: 2026 Wearable Leg vs. 2027 Industrial Biped Platform


ARCHITECTURAL BLUEPRINT & SAFETY INVARIANT SYNTHESIS | STRICT DOMAIN SEPARATION ENFORCED

Kinetic Governance Architectures: Deterministic Safety Invariants (2026–2027)

2026 Wearable Leg Architecture (BPS Eye)

MULTI-FACTOR CONJUNCTION GATES

Human-Centric Clinical Conjunction




Permission is a Live Condition, Not a Checklist

Kinetic eligibility is Issced as a temporary lease; the absence or withdrawal of any single signal immediately severs the output and voids the lease.

Localised Evidentiary Logic


Utilises efficient on-chip hashing to record BPS states and local lease transitions for clinical audit.



2027 Industrial Biped Platform (Nightingale One)

TRIPARTITE HARDWARE INTERLOCK

Deterministic Industrial Interlock



Deterministic Isolation

A hardware-enforced "AND-gate" requiring the simultaneous convergence of Biological, Cryptographic, and Kinetic Inputs.

Industrial-Grade Forensic Vault

A tamper-resistant, isolated Write-Once-Read-Many (WDRM) veoit engineered for post-Incident forensics, decoupled from operational processing liniits.




DIRECT PHYSICS SAFE-HOLD

<1.05 ms Severance Timeline

ABSOLUTE KINETIC ARREST VIA PHYSICS

Halt-First Execution



Direct Rail De-energisation

Upon any fault or release of the hold-to-run switch, power rails drop to 0V immediately, bypassing software 'stop' commands.

Safety by Physics, Not Computation

Safe-Hold is an outcome, not a software execution path; it cannot be exited in-place and requires a full hardware reset and fresh tripartite authorisation to re-arm.

ARCHITECTURAL DIAGNOSTIC MATRIX

	2026 Wearable Leg (Namespace 182)	2027 Industrial Biped (Namespace 181)
Governance Paradigm	Clinical Rehabilitation (BPS Eye)	Deterministic Isolation (Nightingale One)
Master Clocking	100kHz FPGA (Dynamic)	1kHz Monotonic (Deterministic)
Event Ledger	SHA-256 (On-Chip WORM)	SHA-3-512 (Isolated Vault)
Isolation Strategy	Bounded Integration	Galvanic Air-Gap
Failsafe Speed	<1.05 ms	<1.05 ms

The Foundational Premise: Eliminating Agentic Drift



Core Concept: Treating narrative clinical checks or software-generated wellness scores as kinetic authority blurs the critical line between subjective human judgement and local hardware safety envelopes.

The Invariant Rule: Raw narrative or software-generated probabilistic assessments must never directly influence actuator trajectories. The authority to compute must be structurally severed from the authority to actuate.

The Two Orchards: Architectural Paradigm Shift

2026 Wearable Leg Architecture	2027 Industrial Biped Platform
Estate: Tiger Estate (Namespace 182)	Estate: New Horizon Estate (Namespace 181)
Governance Paradigm: Clinical Rehabilitation (BPS Eye)	Governance Paradigm: Deterministic Isolation (Nightingale One Protocol)
Core Philosophy: Human-in-the-loop flexibility. Designed for nuanced, dynamic human interaction where a clinical narrative dictates temporary kinetic eligibility.	Core Philosophy: Halt-First architecture. Designed for heavy industrial mechatronics where absolute, rigid isolation from untrusted external inputs is paramount.


Master Synchronisation: Dynamic Response vs. Absolute Determinism

100kHz FPGA Dynamic Clocking (2026)

Designed for micro-second adjustments required in human gait rehabilitation. Prioritises dynamic mechatronic response to safely assist human biomechanics in real-time.

1kHz Monotonic Master Clock (2027)


Stripped of dynamic variance. Designed for heavy industrial loads where fault-tolerance, predictability, and absolute timing determinism supersede speed.



Core Paradigms: Bounded BPS Narrative vs. Hardware Interlock

The BPS Filter


- Distilling clinical reality to a Bounded Finite State.
- The interface does not independently calculate a diagnostic or therapy score. It converts human-recorded conditions into a strictly binary translation: VERIFIED or NOT VERIFIED.
- Outputs zero torque, velocity, or trajectory commands.



The Funnel of Abstraction

The Tripartite Interlock [801]

- An uncompromising AND-Gate conjunction.
  1. Biological: Iris Scanner [802]
  2. Cryptographic: Console Token [803]
  3. Kinetic: Continuous Hold-to-Run Switch [804]
- Result: Generates a Time-Bounded Motion Authority Lease [303].




AND-Gate Conjunction

Strict Domain Separation: The Boundary of Intent


Namespace 182 / Bounded Integration

- Facilitates nuanced human-robot interaction.
- Clinical inputs share proximity with local safety controllers, separated by rigorous, bounded state-verification software logic.



Namespace 181 / Absolute Perimeter Isolation

- Treats all external inputs as inherently untrusted.
- Relies exclusively on galvanic isolation and physical no-actuation barriers.
- Mathematically and physically prevents arbitrary code execution on motor rails.




The Fail-Safe Paradigm: Physics Over Computation

Safe-Hold is an Outcome, Not an Execution Path.


Computation (The Wrong Way)

Computing a deceleration trajectory requires the software to "decide" to stop, leaving it vulnerable to logic loops and sensor hallucinations.



Physics (The Right Way)

Direct physics-based arrest.



None of the fail-safe triggers require the software to "decide" to stop. Deterministic safety is achieved through the intentional absence of complex fallback software.

Anatomy of a Halt: Software Withhold vs. Hardware Severance


2026 Clinical Architecture

- **Trigger:** Loss, withdrawal, or absence of the bounded BPS verification condition.
- **Mechanism:** Kinetic-eligibility output is immediately withheld.
- **Outcome:** The host apparatus independently removes the local kinetic-permission lease.




2027 Industrial Platform

- **Trigger:** Release of continuous 5kg operator hold-to-run pressure.
- **Mechanism:** Hardware-enforced drop in the tripartite interlock.
- **Outcome:** Physical switch release directly de-energises rails. Motion authority is instantaneously voided.




The Micro-Second Severance Timeline



Absolute kinetic arrest is achieved before harmful momentum can accumulate. The SIL 3 relays provide a sovereign, hardware-only kill switch, executing a full, unoverridable shutdown in under 1.05 milliseconds.

The ‘No-Exit’ Latched Safe-Hold [1202]




- Once Safe-Hold is entered, the state is physically and logically latched.
- There is no ‘in-place’ recovery, software override, or resume function.
- Restarting requires a full, deterministic loop: fresh key read [301], inspected human re-arm, and entirely fresh tripartite authorisation.

Telemetry & Evidence: The Append-Only WORM Ledger

Structurally decoupled from the actuator-authority path.

2026 Baseline


- Utilises on-chip hashing for highly efficient, localised audit trails.
- Records BPS states and local lease transitions.



On-Chip SHA-256 [260]

2027 Industrial Baseline

- A tamper-resistant, WORM (Write-Once-Read-Many) vault engineered for industrial-grade post-incident forensics.
- Completely decoupled from operational processing limits.



Isolated SHA-3-512 WORM Vault [1101]

The Crucial Guarantee: A successful write, failed write, or forensic audit read cannot mathematically or physically confer kinetic authority.

Final Syntihesis: Architectural Diagnostic Matrix

Domain	2026 Wearable Leg Architecture	2027 Industrial Biped Platform
Governance	BPS Eye Clinical Conjunction	Nightingale One Deterministic Halt
Master Clocking	100kHz FPGA (Dynamic)	1kHz Monotonic (Deterministic)
Event Ledger	SHA-256 (On-Chip WORM)	SHA-3-512 (Isolated Vault)
Isolation Strategy	Namespace 182 (Bounded Integration)	Namespace 181 (Galvanic Air-Gap)
Interlock/Failsafe	Eligibility Withhold (Host-Managed)	A10A Tripartite Anchor (Latched Halt)

The Absolute Baseline: Operational Sequences & Invariants



A harmonious sequence where every step acts as a deterministic tripwire. The sequence safely terminates into HOLD whenever physical or local safety prerequisites are absent, withdrawn, or invalid. Every condition must hold true simultaneously. Gravity always wins.


Kinetic Governance Architectures

Comparative Analysis: 2026 Wearable Leg vs. 2027 Industrial Biped

The Two Orchards: Architectural Governance and Safety Invariants

NAMESPACE 182 | 2026
CLINICAL CARE ESTATE

NAMESPACE 181 | 2027
INDUSTRIAL BIPED ESTATE



BPS GOVERNANCE INTERFACE
Filters clinical Blu-Psycho-Social risk screens into bounded finite states, preventing norrative data from influencing actuators.

MECHATRONIC ISOLATION BOUNDARY
A structural separation ensuring the governance layer cannot generate trajectories or independently energize actuators.

KINETIC-PERMISSION CONJUNCTION
Eligibility requires concurrent vobility of BPS verification, human authorisation, and local hardware-safety states.

LINEAGE FIREWALL
Enforces "Leg drives Leg, Humanold drives Humanold" via hardware-enforced translation gateways and air-gaps.

TRIPARTITE HARDWARE INTERLOCK
Isauance of motion leases requires concurrent biological, cryptographic, and kinetic operator switch inputs.


HARDWARE-ENFORCED INVARIANTS
Uses mechanically keyed fistures and fixed non-volable limit set tables to prevent rontime configuration edits.

SIL 3 RELAY SEVERANCE
Redondant safety relays ensure motor-loils are de-enetgised below safe thresholds within specified response windows.

SHARED ARCHITECTURAL INVARIANTS



WORM AUDIT TRAILS
Append-only event registers record all transitions and lesses entirely outside the actuator-authority path.



LATCHED SAFE-HOLD STATE
Faults trigger spring-applied brakes and de energised rails that cannot be exited without a full restart.

COMPARISON OF STATE-CHANGE AUTHORITY

NAMESPACE 102 (Wearable)	NAMESPACE 101 (Platform)
PRIMARY INPUT: Human-Administered BPS Screen	**PRIMARY INPUT:** Tripertite (Bio/Crypto/Kinctic)
SAFETY BARKIER: Mechatronic Isolation Boundary	**SAFETY BARKIER:** Golvanic Isolation Air-Gap
LEASE METHOD: Rounded Mocho Permission	**LEASE METHOD:** Hardware Counter Lease


2026 Wearable Leg Architecture


Estate:	Tiger Estate
Governance Paradigm:	Clinical Rehabilitation (BPS Eye)
Core Philosophy:	Human-in-the-loop flexibility. Designed for nuanced, dynamic human interaction where clinical narrative dictates kinetic eligibility.

2027 Industrial Biped Platform


Estate:	New Horizon Estate
Governance Paradigm:	Deterministic Isolation (Nightingale One Protocol)
Core Philosophy:	Halt-First architecture. Designed for heavy industrial mechatronics where absolute, rigid isolation from untrusted external inputs is paramount.

The Boundary of Intent: Software Gate vs. Galvanic Air-Gap






Authorisation Architectures: The Path to Kinetic Eligibility




Interlock Mechanisms: Conjunction vs. Convergence

BPS Kinetic-Permission Conditioner [160]




A10A Anchor Interlock [801]




Master Synchronisation: Dynamic Response vs. Absolute Determinism


100kHz FPGA Master Clocking.
Designed for the micro-second adjustments required in human gait rehabilitation.
Prioritises dynamic mechatronic response to safely assist human biomechanics in real-time.




1kHz Monotonic Master Clocking.
Stripped of dynamic variance. Designed for heavy industrial loads where fault-tolerance, predictability, and absolute timing determinism supersede speed.



Processing Topologies: Namespace 182 vs. Namespace 181




2026 Wearable Leg Architecture
Namespace 182. Facilitates nuanced human-robot interaction. Clinical inputs share proximity with local safety controllers, separated by rigorous, bounded state-verification software logic.




2027 Industrial Biped Platform
Namespace 181. Total architectural isolation. Treats all external inputs as untrusted. Relies on unidirectional communication [903] and physical no-actuation barriers [901] to prevent arbitrary code execution on motor rails.

Telemetry & Evidence: Append-Only WORM Ledgers



On-Chip SHA-256 [260]

2026 Evidentiary Logic: Utilises on-chip SHA-256 for highly efficient, localised audit trails. Records BPS states and local lease transitions. Explicitly excluded from the actuator-authority path [290].




Isolated SHA-3-512 [1101]


2027 Evidentiary Logic: Mandates an isolated, tamper-resistant SHA-3-512 WORM vault. Engineered for industrial-grade post-incident forensics, completely decoupled from operational processing limits.

The Fail-Safe Paradigm: Software Withhold vs. Hardware Halt

2026 Wearable Leg Architecture



2027 Industrial Biped Platform



Architectural Diagnostic Matrix

Domain	2026 Wearable Leg Architecture	2027 Industrial Biped Platform
Governance	BPS Eye Clinical Conjunction	Nightingale One Deterministic Halt
Master Clocking	100kHz FPGA (Dynamic)	1kHz Monotonic (Deterministic)
Event Ledger	SHA-256 (On-Chip WORM)	SHA-3-512 (Isolated Vault)
Isolation Strategy	Namespace 182 (Bounded Integration)	Namespace 181 (Galvanic Air-Gap)
Interlock/Failsafe	Eligibility Withhold (Host-Managed)	A10A Tripartite Anchor (Latched Halt)

Final Synthesis: Deployment Topologies

Tiger Estate


The 2026 Architecture remains the absolute standard for clinical, human-in-the-loop environments. It provides the essential mechatronic flexibility required for patient rehabilitation while retaining strict, bounded BPS assessment layers.

New Horizon Estate

The 2027 Architecture is exclusively mandated for non-agentic industrial deployments. Where the environment is untrusted and kinetic mass is lethal, its hardware determinism and uncompromising tripartite isolation are non-negotiable.

Kinetic Governance Architectures:


2027 Industrial Biped Platform
(New Horizon Estate) / Nightingale One Protocol



The Two Orchards: Architectural Paradigm Shift

2026 Wearable Leg Architecture	2027 Industrial Biped Platform
Estate: Tiger Estate (Namespace 182)	Estate: New Horizon Estate (Namespace 181)
Governance Paradigm: Clinical Rehabilitation (BPS Eye)	Governance Paradigm: Deterministic Isolation (Nightingale One Protocol)
Master Clocking: 100kHz FPGA (Dynamic)	Master Clocking: 1kHz Monotonic (Deterministic)
Core Philosophy: Human-in-the-loop flexibility. Designed for nuanced, dynamic human interaction where a clinical narrative dictates kinetic eligibility.	Core Philosophy: Halt-First architecture. Designed for heavy industrial mechatronics where absolute, rigid isolation from untrusted external inputs is paramount.
Synthesis Insight: Where the environment is untrusted and kinetic mass is lethal, hardware determinism and uncompromising tripartite isolation are non-negotiable.	

The Boundary of Intent: Absolute Perimeter Isolation



Total architectural isolation. The Namespace 181 architecture treats all external inputs as inherently untrusted. It relies exclusively on galvanic isolation and physical no-actuation barriers to mathematically prevent arbitrary code execution on motor rails.


Master Synchronisation: Dynamic vs. Deterministic

100kHz FPGA Dynamic Clocking (2026)

Designed for micro-second adjustments required in human gait rehabilitation. Prioritises dynamic mechatronic response to safely assist human biomechanics in real-time.


1kHz Monotonic Master Clock (2027)

Stripped of dynamic variance. Designed for heavy industrial loads where fault-tolerance, predictability, and absolute timing determinism supersede speed.




Blueprint of Determinism


The Tripartite Hardware Interlock



Kinetic permission is a live condition, not a checklist. All requisite states must be concurrently valid. The absence of any single signal immediately severs the output, voiding the lease.


Human-in-the-Loop Tactile Fail-Safe





Trigger:	Mechanism:	Outcome:
Release of continuous 5kg operator hold-to-run pressure.	A hardware-enforced drop in the tripartite interlock [801].	The physical switch release directly de-energises rails. Motion authority is instantaneously voided.


The Micro-Second Severance Timeline




Absolute kinetic arrest is achieved before harmful momentum can accumulate. The SIL 3 relays provide a sovereign, hardware-only kill switch, executing a full shutdown in under 1.05 milliseconds.

Safe-Hold is an Outcome, Not an Execution Path

Computation (The Wrong Way)
Computing a deceleration trajectory.




Physics (The Right Way)
Direct physics-based arrest.



None of the fail-safe triggers require the software to 'decide' to stop. Nightingale One does **not compute** a deceleration trajectory. Deterministic safety is achieved through the intentional absence of complex fallback software.

The ‘No-Exit’ Latched Safe-Hold




Once Safe-Hold is entered, the state is physically and logically latched.

There is no ‘in-place’ recovery, override, or resume function.

Restarting requires a full deterministic loop: fresh key read, inspected human re-arm, and entirely fresh tripartite authorisation.

Telemetry & Evidence:
The Append-Only WORM Ledger


2026 Baseline



On-Chip SHA-256

Utilises on-chip hashing for highly efficient, localised audit trails.


2027 Industrial Baseline



Isolated SHA-3-512 WORM Vault

A tamper-resistant, WORM (Write-Once-Read-Many) vault engineered for industrial-grade post-incident forensics. Completely decoupled from operational processing limits and explicitly excluded from the actuator-authority path.


Final Synthesis:
The Operational Sequence



A harmonious sequence where every step acts as a deterministic tripwire. The sequence safely terminates into HOLD whenever physical or local safety prerequisites are absent, withdrawn, or invalid. Every condition must hold true simultaneously. Gravity always wins.

Policy as Physics


Advanced Kinetic Governance & Exacting Physical Patient Transfer Protocols



Gemini Notebook

16:9 Clinical Blueprint

The Threat




Agentic Drift & TOCTOU Exploits

Relying on neural network inference introduces severe vulnerability. Latency allows the physical reality to change before a motor fires (Time of Check to Time of Use). Algorithmic hallucinations translate directly into physical injury.

Air-Gap

The Solution



Mechatronic Determinism

Software logic is strictly advisory. Silicon logic is absolute. True patient safety requires replacing fallible programmable software policies with immutable physical hardware logic.

Gemini Notebook

M=0 Observational Stratum
(The Eyes & Mind)



LiDAR



Radar



Pressure Sensors

Structural demotion of sensing. Raw data is purged into a 96-cell anonymised voxel grid.

The BPS Interface: Translates clinical Bio-Psycho-Social risk into a finite gating condition:

VERIFIED | ~~**NOT VERIFIED**~~

It does **NOT** compute a **diagnostic score, therapy score**, or actuator trajectory.

Silicon Privacy Wall & & Galvanic Isolation Air-Gap

M>0 Kinetic Execution Stratum
(The Muscle)



Actuators




Motor Rails



High-Torque Drives

Observation data cannot bridge the gap to independently energise an actuator. Software holds zero actuator execution rights.



Structural demotion of sensing. Observation data cannot bridge the gap to independently energise an actuator.

Gemini Notebook

The Machine Laws: Hardware Pre-Actuation Safety Fabric



Zero-Velocity Buffer

Verifies the system is completely static before any motion begins.

A10a Enforcement Anchor


Driven by a monotonic 1 kHz master clock. Ties execution to a strict physical pulse, stripping software of the ability to manipulate execution windows.

Kinematic Constraint Layer (KCL)

Absolute physical limits (jerk invariants, acceleration caps) are burned directly into silicon. Ordinary application software is structurally incapable of enlarging them.

Gemini Notebook

Authorising Kinetic Motion




Caregiver Cryptographic Token
(Physical console key)

Continuous 5kg Physical Force
(Normally-open kinetic operator switch).

The Time-Bounded Lease


Once authorised, a bounded kinetic lease is issued, constrained by elapsed time or a maximum motion quantum.



Lease Expiry = Zero Voltage.
Software cannot self-renew; fresh physical re-validation is required.


Gemini Notebook

The Fail-Closed Response



The U7 Relay Severance


Hardwired relays physically sever the copper electrical paths supplying the motors in <1.05 ms. Bypasses software entirely.



Inert Fail-Closed Safe-Hold


Triggers mechanical restraint to **freeze** joints in their exact current position. Exiting requires a total physical reset to zero-velocity.





The WD117 WORM Ledger

Write-Once-Read-Many evidentiary log chained with SHA-3-512 hashes. Sits entirely outside the actuator authority path.



Gemini Notebook

The Transfer Methodology Matrix

Transfer Type	Patient Profile	Key Equipment	Time Allocation
SARA Stedy (1-way)	Minimal assist, stable upper body, able to stand, no knee flexion restrictions. Weight strictly <182kg (400 lbs).	SARA Stedy	15 mins
Lateral Transfer (2-way)	Bed-bound, moving to stretcher or bath trolley.	Patslide, slide sheets	15 mins
Mechanical Hoist (2-way)	High dependency, unable to weight-bear, or cognitively impaired/uncooperative.	Minstrel Patient Hoist, sized sling	50 mins
Synchronised Two-Man Lift	Equipment failure / emergency manual handling of last resort.	N/A	N/A

Gemini Notebook


SARA Stedy: Hard Criteria & Anatomy of a Safe Transfer

The Authorisation Filter Funnel

- ✓ 1. Weight strictly under 182 kg (400 lbs)
- ✓ 2. Can stand with minimal assistance
- ✓ 3. Trunk control (upper body stable)
- ✓ 4. Absolutely no knee flexion restrictions

ACTION RULE: If any single condition is not met, the SARA Stedy is contraindicated. Seek alternative (e.g., Hoist).

Anatomy of a Safe Transfer



Upper Limbs: Patient must actively hold the handlebars. Staff must NEVER pull the resident by the arms to force them to stand.

Pelvis/Core: Patient must NOT rest weight on the seat flaps while in motion (flaps must be completely down before sitting).

Lower Limbs: Both knees MUST rest securely in contact with the kneepad. (Skipping guarantees a fall).

Base: Wheel locks MUST be engaged.

Gemini Notebook

Diagnostic Fault-Finding: Recognising Ergonomic Failures

The Procedural Error	The Clinical Consequence	The Clinical Fix
✗ Pushing the SARA Stedy flush against the bed frame before transfer.	Patient's legs become trapped or crushed upon standing.	✓ Leave adequate clearance gap and open the leg spreader fully.
✗ Lifting a patient rapidly to minimise transfer time.	Loss of synchronised movement, resulting in muscle strain for staff and severe instability for the patient.	✓ Execute smooth, coordinated movements utilising verbal timing cues ('1, 2, 3, Lift').
✗ Applying a hoist sling without checking skin integrity.	Undetected pressure injuries, skin tears, or hidden bruising.	✓ Perform a mandatory visual skin check during the rolling and setup phase.

Gemini Notebook

The Synchronised Two-Man Lift

Manual Handling of Last Resort (Indicated only when mechanical equipment is non-functional).

Helper 1 (Positioned behind patient)

Setup: Adjust bed slightly higher than wheelchair.

Action: Initiate long sitting. Position one leg on bed, one between bed and wheelchair.

The Grip: Execute a through-arm grip, grasping the patient's forearms with opposite hands. Absolute prohibition on pulling by the arms or elbows.

Execution: Deliver clear verbal timing cues ('1, 2, 3, Lift').

Helper 2 (Positioned at legs)

Setup: Remove armrests/footplates. Angle wheelchair near bed and lock all brakes.

Action: Assist Helper 1 to sit patient up.

The Grip: Support legs with one arm under the thigh and the other under the lower leg, holding them close to the body.

Execution: Lift in perfect synchronicity with Helper 1's cues.

Gemini Notebook

Human Laws: Absolute Non-Negotiables

The Universal Pre-Flight Protocol

- ☐ Verify patient cognitive and weight-bearing readiness.
- ☐ Clear all environmental hazards and obstacles.
- ☐ **Hardware Lock:** Ensure ALL brakes on beds, wheelchairs, and commodes are fully locked.
- ☐ Adjust surface heights to utilise gravity (bed slightly higher than destination).

In-Flight & Post-Transfer Non-Negotiables

- ☐ **Orthostatic Management:** Continuous observation throughout the transfer to detect dizziness or hypotension. Never leave a patient suspended in a hoist or dangling mid-air.
- ☐ **Orthostatic Alignment:** Hips must be seated firmly at the very back of the chair.
- ☐ **Final Lock:** Confirm armrests, footplates, and safety accessories are securely re-engaged before departing.

Gemini Notebook

The 100% Competency Mandate

Rule 1: The Single Prompt Limit

During assessment, evaluators will provide a maximum of 1 prompt for a provide a maximum of 1 prompt for a vallication a non-samee per transfer. No prompts are provided for non-safety issues.

Rule 2: The Hard Stop

Assessment ceases immediately if safety is compromised a second time (whether a repeat of the first error or a new safety violation).


Rule 3: Zero Margin for Error

No 2nd try option. Technical issues serve as learning points, but safety failures result in an immediate ‘Not Competent’ (NC) grade for the entire task. — end of the first miring warms. A patient’s safety allows no second attempts in physical reality.

Gemini Notebook

The Standard of Precision Care

Machine logic and human clinical practice share the exact same safety coin:
Inaction as the default until safety is explicitly verified.



Establish the Baseline

Machine: Zero-Velocity Buffer & A10a Enforcement Anchor.

Human: Universal Pre-Flight Protocol & BPS Assessment.

Synthesis: Safe handling begins before movement. Verify physiological stability and account for physical restrictions.

Filter the Intervention

Machine: Kinematic Constraint Layer (KCL).

Human: Transfer Methodology Matrix & SARA Stedy Funnel.

Synthesis: Match the physical action to the exact verified capability.

Execute the Geometry

Machine: Tripartite Interlock & Time-Bounded Lease.

Human: Synchronised Lifts & Through-Arm Grips.

Synthesis: Adhere strictly to designed biomechanics. Respect the limits of both the human body and the mechanical equipment.

Gemini Notebook